Data Sheet

We make sure

FUJITSU SIEMENS COMPUTERS

SCALEOVIEW D22W-1
22 Inch LCD widescreen Display

Issue   January 2008

Pages   2

An attractive price doesn't mean that you have to compromise on style or performance. The SCALEOVIEW D22W-1 widescreen display offers best performance for the home office and multimedia, such as photo editing, gaming and watching the latest DVD. With its extremely slim and stylish design, the SCALEOVIEW D22W-1 fits perfectly into your home environment.

Highlights

- 22-inch widescreen display for a perfect viewing experience at high resolution
- Stylish black design with a piano black glossy front
- DVI-D input supports HDCP
- Best performance to an affordable price
- Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use OSD menu

Ergonomics

- Optimum flicker-free and distortion-free picture
- Excellent color purity
- Well balanced brightness uniformity
- Excellent Advanced Contrast Ratio (2000:1)
- Space saving design

Technical highlights

- 22" (55.9 cm) LCD widescreen display
- Excellent contrast (ACR)   2000:1
- Brightness   300 cd/m^2
- Fast response time (typ.)   5 ms
- Internal power supply

Reliability

- Low power consumption
- Power management according to EPA
- Guaranteed quality and stability

Visible screen diagonal	22 inch (55.9 cm)
Resolutions Pixels Pixels* * expanded	1680 x 1050 1280 x 768
Picture size	473.76 x 296.1 mm
Colors	16.7 million
Pixel Pitch	0.282 mm
Frequencies Horizontal Vertical	31.5 - 83 kHz 56 - 76 Hz
Brightness (typical)	300 cd/m²
Contrast (ISO) Advanced Contrast Ratio	1000:1 2000:1
Viewing angle (cr<=5) Horizontal Vertical	170° 160°
Response time (typical)	5 ms
Plug and Play	VESA DDC2B
Setting options Brightness (Back light control) Contrast, Volume control Picture position (horizontal and vertical), H-size, Phase, Color temperature and individual color setting Auto-adjust (direct access key) Activate factory settings Menu language	
OSD Language English, German, Spanish, Portuguese, French, Italian, Russian, Swedish, Dutch, Finnish, Danish, Norwegian, Polish, Chinese, Japanese	
Base Tilt angle	-5° / +15°
Video input	1x D-SUB, 1x DVI-D (HDCP support)
Audio input / output Audio signal input Audio output	3.5 mm stereo phone jack 1 W (L) + 1 W (R)

Electrical values (internal power supply) Rated voltage Frequency Power draw Max. Stand by Protection class	100 - 230 V 50 - 60 Hz <55 W < 2 W 1
Temperatures/ dimensions/ weight Ambient temperature (to IEC721): Working (recommended) Storage Dimensions (H x W x D): (with stand) Weight (Monitor only)	5°C to 35°C -20°C to 60°C 424 x 510 x 202 mm 4.94 kg
Reliability MTBF (demonstrated) Lifetime of LCD backlight (brightness > 50 % of original brightness)	70,000 h 50,000 h
Compliance with standards Product safety Ergonomics Radiation immunity and RFI suppression	EN60950 GS mark ISO13406-2 (Pixel fault class II) CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3)
Accessories Power cable (1.8 m)* Data cable (1.8 m)* Audio cable (1.8 m)* * detachable on display	1x wall socket (Euro-Schuko-Type CEE7) D-SUB (15-pin) DVI-D (19-pin) 3.5 mm stereo phone jack
Special features	Standardized mounting interface according VESA FPMPMI (100 mm) Kensington Lock
Order code **EAN**	S26361-K1230-V170 433364 3137588